

Report No. PNS220526258 07011

Material Safety Data Sheet

Name of Products:	Lithium-ion Battery	
Applicant:	Maxima Solar	
Factory:	Shop 5&6, 7 States building Baniyas Square, Deira, Dubai, UAE	

Report No. : PNS220526258 07011 Page 2 of 13

1. Identification of the product and supplier				
Name of goods	Lithium-ion Battery			
Type/Model	SBM48Li100			
Rating	48V, 100Ah, 4800Wh			
Commissioned by	ZHANGZHOU HUAWEI POWER SUPPLY TECHNOLOGY CO., LTD			
Commissioner address	LIEYU INDUSTRIAL DISTRICT, YUNXIAO, ZHANZHOU, FUJIAN, CHINA Guangdong Province, P.R. China			
Manufacturer's name	ZHANGZHOU HUAWEI POWER SUPPLY TECHNOLOGY CO., LTD			
Manufacturer address	LIEYU INDUSTRIAL DISTRICT, YUNXIAO, ZHANZHOU, FUJIAN, CHINA Guangdong Province, P.R. China			
Inspection according to	UN "Recommendations on the TRANSPORT OF DANGEROUS GOODS"			
Emergency telephone call	+86-596-8991888			
Receiving date: 2022-05-24		Date of issue: 2022-06-15		



2. Composition Information				
Chemical Composition	Chemical Formula	Weight(%)	CAS Number	
Lithium Iron Phosphate	LiFePO ₄	30-45	15365-14-7	
Carbon	С	2-4	7440-44-0	
Graphite	C ₂₄ X ₁₂	13-19	7782-42-5	
Aluminium Foil	Al	3-5	7429-90-5	
Copper	Cu	4-8	7440-50-8	
Ethylene Carbonate	C ₃ H ₄ O ₃	3-5	96-49-1	
Dimethyl Carbonate	C ₃ H ₆ O ₃	5-10	616-38-6	
Nickel	Ni	8-12	7440-02-0	

3. Hazards Identification		
Explosive risk	This article does not belong to the explosion dangerous goods	
Flammable risk	This article does not belong to the flammable material	
Oxidation risk	This article does not belong to the oxidation of dangerous goods	
Toxic risk	This article does not belong to the toxic dangerous goods	
Radioactive risk	This article does not belong to the radiation of dangerous goods	
Mordant risk	This article does not belong to the corrosion of dangerous goods	
other risk	This article is the Li-ion Battery Pack, Watt hour rate 4800Wh. Which belong to the Class 9 of dangerous goods.	



Report No.: PNS220526258 07011 Page 4 of 13

4. First aid measures

Eye

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

Inhalation

Remove from exposure and move to fresh air immediately. Use oxygen if available.

Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

5. Fire-fighting measures

Flash Point: N/A.

Auto-Ignition Temperature: N/A.

Extinguishing Media: Water, CO2.

Special Fire-Fighting Procedures: Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Cell may vent when subjected to excessive heat-exposing battery contents.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.



Report No. : PNS220526258 07011 Page 5 of 13

6. Accidental release measures

Steps to be Taken in case Material is Released or Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

Waste Disposal Method

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.

7. Handling and storage

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire.

Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

幸

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures.

Do not short or install with incorrect polarity.





Report No. : PNS220526258 07011 Page 6 of 13

8. Exposure controls/personal protection

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Protective Gloves

Not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.



Report No.: PNS220526258 07011

Page 7 of 13

9. Physical and chemical properties

Appearance: Quadrate shape

Odour: If leaking, smells of medical ether.

Odor Threshold: Not applicable.

pH: Not applicable.

Melting Point/freezing point: Not applicable.

Initial boiling point and Boiling range: Not applicable.

Flash Point: Not applicable.

Evaporation rate: Not applicable.

Flammability (solid, gas): Not applicable.

Upper/lower flammability or explosive limits: Not applicable.

Vapor Pressure: Not applicable.

Vapor Density: Not applicable.

Relative density: Not applicable.

Solubility (water): Not applicable.

Solubility (other): Not applicable.

n-octanol/water partition coefficient: Not applicable.

Auto-ignition temperature: Not applicable.

Decomposition temperature: Not applicable.



Report No. : PNS220526258 07011 Page 8 of 13

10. Stability and reactivity

Stability: Product is stable under conditions described in Section 7.

Conditions to avoid: Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.

Materials to avoid: Oxidising agents, alkalis, water.

Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.

Hazardous Polymerization: N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

11. Toxicological information

Signs & symptoms: None, unless battery ruptures.

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

Inhalation: Lung irritant.

Skin contact: Skin irritant

Eye contact: Eye irritant

Ingestion: Poisoning if swallowed

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target organs nerves, liver and kidneys.



Report No. : PNS220526258 07011 Page 9 of 13

12. Ecological information

Mammalian effects: None known at present.

Eco-toxicity: None known at present.

Bioaccumulation potential: Slowly Bio-degradable.

Environmental fate: None known environmental hazards at present.

13. Disposal consideration

Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

14. Transport information

Label for conveyance: The Class 9—Lithium Battery hazard label, the Cargo aircraft Only Label, The Class

9—Miscellaneous Dangerous Goods

UN☑号:UN3480 或 UN3481 或 UN3171 **UN Number:** UN3480 or UN3481 or UN3171

Packing Group: Group II (Not apply to PI952 and PI967 Section I)


EmS No: F-A, S-I

Marine pollutant: No

Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises: No further information.

UN Proper Shipping name:. 1) Lithium ion batteries; 2) Lithium ion batteries packed with equipment; 3) Lithium ion batteries contained in equipment. (including Lithium ion polymer); 4) Batteries powered vehicle

Transport hazard class(es): The goods shall be complied with the requirements of Section IA of Packing Instructions 965 or Section I of Packing Instructions 966~967 of 63rd DGR Manual of IATA (2022 Edition) and IMDG CODE (Amdt. 40-20) 2020 Edition, including the passing of the UN38.3 test.



Report No.: PNS220526258 07011

Page 10 of 13

15. Regulation information

Law information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substance Control Act》(TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title⊠ (302/311/312/313)》 (SARA)

《Resource Conservation and Recovery Act》(RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and local laws.

16. Other information

This file is only effective to the batteries (SBM48Li100) provided by ZHANGZHOU HUAWEI POWER SUPPLY TECHNOLOGY CO., LTD which manufactured by ZHANGZHOU HUAWEI POWER SUPPLY TECHNOLOGY CO., LTD The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. GUANGDONG UTL CO., LTD. (UTL) doesn't assume responsibility for any damage or loss because of misuse of batteries.





Photos




Figure 1 Overall view I of battery




Figure 2 Overall view II of battery



Report No. : PNS220526258 07011 Page 13 of 13

Important

	important			
1.	Nobody is allowed to photocopy or partly photocopy this test report without written permission of UTL.			
2.	The test report is invalid without the signatures of Approver, Reviewer and Tester.			
3.	The test report is invalid if altered.			
4.	Objections to the test report must be submitted to UTL within 15 days.			
5.	Throughout this report a point is used as the decimal separator.			
6.	The test report is valid for the tested samples only.			
7.	The test report does not grant applicant the use of UTL name, trademark or label.			
8.	UTL's liability under no circumstance will exceed the testing fee received from applicant for test conducted hereof this testing report.			
The	e test data and results do not have social proof function.			

****** End of Test Report ******



