



–Data Center Product Line –

LEPTON Series



Visit Our Website
www.maxima.solar



Call Us
+971 4 2231185



Our Address
Shop 5&6, 7 States building Baniyas
Square, Deira, Dubai, UAE

LEPTON Series

600 ~ 3000VA



General introduction

This UPS is specially designed for Personal Computer with multi-functions. Its light weight, compact design perfect fits to the limited working environment. The line of UPS is equipped with two boost and one buck AVR to stabilize wide input voltage range. It is also built-in with DC start function. This function enables the UPS to be started up without AC power supply. Although it's a small UPS, The main features of UPS are listed below:

Features

- Line Interactive UPS with simulated sinewave output
- Excellent microprocessor control guarantees high reliability (internal self-diagnostic technology)
- Boost and buck AVR for voltage stabilization (wide input range with two boost and one buck control)
- Auto restart while AC is recovering
- Cold start function



Two kinds of color LCD display

LED display

- Off-mode charging
- Fast intelligent battery recharge function
- Generator compatible
- Offering LED and LCD panels for selections
- Optional USB/RS232 communication port and RJ11/RJ45 protection

- ① AC input
- ② Output socket
- ③ USB & RJ11 communication
- ④ USB & RS232 communication
- ⑤ RJ45



Optional socket



Rear Panel

MODEL	LEPTON 800	LEPTON 1K	LEPTON 1.5K	LEPTON 2K
Capacity(VA/Watts)	800 / 480	1000 / 600	1500 / 900	2000 / 1200

INPUT

Voltage	220/230/240Vac
Voltage Range	140-300Vac
Frequency Range	50/60Hz (auto sensing)

OUTPUT

AC Voltage Regulation (Batt.Mode)	±10%
Frequency Range (Batt.Mode)	50/60Hz ± 1 Hz
Transfer Time	Typical 4-8ms, 13ms Max.
Waveform (Batt.Mode)	Simulated Sinewave

BATTERY

Battery Voltage	12Vdc	24Vdc		
Battery Type & Number	12V / 9AH x 1	12V / 7AH X 2	12V / 9AH X 2	12V / 9AH X 2
Typical Recharge Time	4-6 hours recover to 90% capacity	6-8 hours recover to 90% capacity		

INDICATORS

LED Display(LED version)	AC Mode, Battery Mode, Overload, fault	N/A
LCD Display(LCD version)	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Fault and Battery Low	

PROTECTION

Full Protection	Short circuit, Overload, Overcharge and overdischarge protection
-----------------	--

ALARM

Battery mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Battery Replacement Alarm	Sounding every 2 seconds
Fault	Continuously sounding

MANAGEMENT

Communication port	USB or RS232(Supports Windows 2000/2003/XP/Vista/2008, Windows 7, Linux, Unix, and MAC)
--------------------	---

OPERATING ENVIRONMENT

Humidity	0-90% RH @0-40° C (non-condensing)	
Noise Level	Less than 45dB	Less than 55dB

PHYSICAL

Approx. Dimension D * W * H (mm)	298*101*142	353*149*162	380*158*198	
Approx. Net Weight (kgs)	Approx. 4.9	Approx. 7.8	Approx. 10.1	Approx. 10.1

Specifications are subject to change without prior notice.