

ETN125NHG01B

Catalog Number: ETNPV-20A10 FUSE

Maxima Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 125A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body



General specifications

Product Name	Catalog Number
Maxima Bussmann series low voltage NH Fuse	ETN125NHG01B
	EAN
	5027590429979
UPC	Product Length/Depth
051712626019	135 mm
Product Height	Product Width
57.8 mm	29.55 mm
Product Weight	Compliances
295 g	RoHS Compliant
	CE Marked
Certifications	Model Code
IEC 60269-1	NH FUSE 125A 500V GG/GL SIZE 01
IEC 60269-2	
DIN 43620	

Electrical data

Amperage Rating

125 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class gG/gL

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH01

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

Microswitch 170H0235

Resources

Catalogues

CA134002EN

NH Fuse links, bases and gear

Compliance information

CE NH Size 01/1, 500V fuse-links

UKCA NH Size 01/1, 500V fuse-links

Multimedia

Maxima Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

ETN125NHG01B

Bur Dubai Office:

Showroom # 19, SUQ Al Kabeer Building,
Bur Dubai, Dubai, UAE

Deira Office:

Showroom # 5 & 6, 7 States Building
Baniyas Square, Deira, Dubai, UAE