

# ETN25NHG01B

Catalog Number: ETN25NHG01B

Maxima Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 25A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Maxima Bussmann series low voltage NH Fuse	ETN25NHG01B
	<b>EAN</b>
	5027590471015
<b>UPC</b>	<b>Product Length/Depth</b>
051712625920	135 mm
<b>Product Height</b>	<b>Product Width</b>
57.8 mm	29.55 mm
<b>Product Weight</b>	<b>Compliances</b>
295 g	CE Marked
	RoHS Compliant
<b>Certifications</b>	
IEC 60269-1	
IEC 60269-2	
DIN 43620	

## Electrical data

### Amperage Rating

25 A

### Voltage rating

500 V

### Voltage type

AC

### Breaking capacity

120 kA

### Class

Class gG/gL

### Frequency rating - min

45 Hz

### Frequency rating - max

62 Hz

## Product specification

### Fuse size

NH0

### Insulated metal gripping lugs (IMGL)

No

## Accessories

### Suitable for

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

## Resources

### Catalogues

CA134002EN

NH Fuse links, bases and gear

### Compliance information

CE NH Size 01/1, 500V fuse-links

UKCA NH Size 01/1, 500V fuse-links

### Multimedia

Maxima Bussmann – NH fuse link portfolio

### Presentations

NH Overview Video

### Technical data sheets

10164 NH 500 Volts gG

### Technical service bulletins

Datasheet - ETN25NHG01B

#### Bur Dubai Office:

Showroom # 19, SUQ Al Kabeer Building,  
Bur Dubai, Dubai, UAE

#### Deira Office:

Showroom # 5 & 6, 7 States Building  
Baniyas Square, Deira, Dubai, UAE