

# ETN50NHG000B

Catalog Number: ETN50NHG01B



Maxima Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 50A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate, Ceramic body

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Maxima Bussmann series low voltage NH Fuse	ETN50NHG000B
	<b>EAN</b>
	5027590483148
<b>UPC</b>	<b>Product Length/Depth</b>
051712625838	79 mm
<b>Product Height</b>	<b>Product Width</b>
51 mm	21 mm
<b>Product Weight</b>	<b>Compliances</b>
131 g	RoHS Compliant
	CE Marked

## Certifications

IEC 60269-1  
IEC 60269-2  
DIN 43620

## Electrical data

### Amperage Rating

50 A

### Voltage rating

500 V

### Voltage type

AC

### Breaking capacity

120 kA

### Class

Class gG/gL

### Frequency rating - min

45 Hz

### Frequency rating - max

62 Hz

## Product specification

### Fuse size

NH000

### Insulated metal gripping lugs (IMGL)

No

## Accessories

### Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

## Resources

### Catalogues

CA134002EN

NH Fuse links, bases and gear

### Compliance information

CE NH Size 000, 500V fuse-links

UKCA NH Size 000, 500V fuse-links

### Multimedia

Maxima Bussmann – NH fuse link portfolio

### Presentations

NH Overview Video

### Technical data sheets

10164 NH 500 Volts gG

#### Bur Dubai Office:

Showroom # 19, SUQ Al Kabeer Building,  
Bur Dubai, Dubai, UAE

#### Deira Office:

Showroom # 5 & 6, 7 States Building  
Baniyas Square, Deira, Dubai, UAE