

ETN63NHG000B

Catalog Number: ETN63NHG000B



Maxima Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 63A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate, Ceramic body

General specifications

Product Name	Catalog Number
Maxima Bussmann series low voltage NH Fuse	ETN63NHG000B
	EAN
	5027590485326
UPC	Product Length/Depth
051712625845	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Compliances
119.333 g	RoHS Compliant
	CE Marked
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	

Electrical data

Amperage Rating

63 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class gG/gL

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH000

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Resources

Catalogues

CA134002EN

NH Fuse links, bases and gear

Compliance information

CE NH Size 000, 500V fuse-links

UKCA NH Size 000, 500V fuse-links

Multimedia

Maxima Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

10164 NH 500 Volts gG

Bur Dubai Office:

Showroom # 19, SUQ Al Kabeer Building,
Bur Dubai, Dubai, UAE

Deira Office:

Showroom # 5 & 6, 7 States Building
Baniyas Square, Deira, Dubai, UAE