

SOLARA-003-02 - All In Two Classic Solar Street Light - 2 Way

IP65 SRNE GOTION CE

PRODUCT FEATURES



LIGHTING	LED power	: 60W + 60W
	LED chip type	: Philips SMD 5050
	Luminous flux	: 11000 lm + 11000 lm
	Luminous efficiency	: 180 lm/w
	LED Quantity	: 60Pcs Each
	CRI	: 70
	Heat Sink	: Yes
	CCT	: 1800K ~ 6000K, Ideal 4000K
	Sensor	: No
	Lifespan	: 5 Years
	Work Mode	: Programmable/ Supplied with pre programmed First 6hours 100% then 6hours 50%
	Size	: Ø 450MM X H 277MM
		
SOLAR PANEL	Silicon Type	: Monocrystalline Silicon
	PV Power	: 36V, 260W
	Life span	: 10 Years
	Cables	: 3 Meters
	PV Dimension	: L 1134MM X W 1303MM X T 30MM
	Structure	: With Frame
BATTERY	Type	: LiFePO4 Battery
	Voltage	: 25.6V
	Capacity	: 60Ah
	Cell Type	: 32135, 15AH, 3.2V, 8 in row 2 level, 32Pcs
	Working Temperature	: Charge -10 ~ 70°C / Discharge -20 ~ 70°C
	Lifespan	: > 3000 Cycle
	Brand	: Gotion High Tech 32135, 15AH, 3.2V A+ Grade
CONTROLLER	Brand	: SRNE
	Type	: MPPT
	Model	: DM 160
	Lifespan	: 5 Years
GENERAL	Material - Street Light	: Aluminum + Lens + PC Diffuser
	Material - Battery Pack	: Aluminum
	IP/ IK Rating	: IP65/ IK08
	Battery Pack	: 3 pin plug for Light & Solar Panel, Switch & Charging Indicator
	Battery Holder	: Rotatable
	Street Light	: Not Tilttable
	Preferable Pole Height	: 5 - 8Mtrs
	Warranty	: 5 Years for the whole system

SOLARA-003-02 - All In Two Classic Solar Street Light - 2 Way


IP65 SRNE GOTION CE

DIMENSIONS

Classic Street Light



Solar Panel



APPLICATIONS

Community Roads, Villas, Farmhouses, Parks & Walkways.



PACKING INFORMATION

1 Box = 1 Pcs

5.2Kg

L 490MM X W 490MM X H 315MM

AVAILABLE COLOUR

Black

