

SOLARA-004-01 - All In Two Solar Flood Light

IP65 LUMIAX GOTION CE

PRODUCT FEATURES

LIGHTING	LED power	: 100W + 100W
	LED chip type	: Philips SMD 5050
	Luminous flux	: 17000 lm + 17000 lm
	Luminous efficiency	: 170 lm/w
	LED Quantity	: 200 Pcs (50Pcs Each Module)
	CRI	: 70
	Heat Sink	: Yes
	CCT	: 1800K ~ 6000K, Ideal 4000K
	Sensor	: No
	Lifespan	: 5 Years
	Work Mode	: Programmable/ Supplied with pre programmed First 6hours 100%
	Size	: L 350MM X W 250MM X H 150MM
SOLAR PANEL	Silicon Type	: Monocrystalline Silicon
	PV Power	: 36V, 260W
	Life span	: 10 Years
	Cables	: 3 Meters
	PV Dimension	: L 1134MM X W 1303MM X T 30MM
	Structure	: With Frame
BATTERY	Type	: LiFePO4 Battery
	Voltage	: 25.6V
	Capacity	: 60Ah
	Cell Type	: 32135, 15AH, 3.2V, 8 in row 2 level, 32Pcs
	Working Temperature	: Charge -10 ~ 70°C / Discharge -20 ~ 70°C
	Lifespan	: > 3000 Cycle
CONTROLLER	Brand	: LUMIAX
	Type	: MPPT
	Model	: LUMIAX 2075
	Lifespan	: 5 Years
GENERAL	Material - Street Light	: Aluminum + Lens + PC Diffuser
	Material - Battery Pack	: Aluminum
	IP/ IK Rating	: IP65/ IK08
	Battery Pack	: 3 pin plug for Light & Solar Panel, Switch & Charging Indicator
	Battery Holder	: Rotatable
	Street Light	: 90° Tilttable Up/ Down
	Preferable Pole Height	: 5 - 8Mtrs
	Warranty	: 5 Years for the whole system




SOLARA-004-01 - All In Two Solar Flood Light


IP65 LUMIAX GOTION CE

DIMENSIONS

Classic Street Light



Solar Panel



APPLICATIONS

Farmhouses, Parking Areas, Parks, Industrial Sites, Warehouses & Playgrounds.



PACKING INFORMATION

1 Box = 1 Set

7Kg

L 390MM X W 320MM X H 290MM

AVAILABLE COLOUR

Black

