



SOLAR LIGHTING

SOLARA SERIES

Go Farther with Solar


*** Bright. Clean. Limitless ***

Email: info@ramopower.com

Address: Unit 16G, Milland Road Industrial Estate,
Milland Rd, Neath SA11 1NJ, United Kingdom

Tel: +44 1639 633933

Item	Battery pack specifications 01	Battery pack specifications 02
Battery pack size	470*390*130mm	470*390*130mm
Battery voltage &wattage	60Ah,12.8V	60Ah,25.6V
Battery brand & model	Gotion High Tech 32135 15AH, 3,2V A+ Grade	Gotion High Tech 32135 15AH, 3,2V A+ Grade
Battery cell size	φ33.6*139.7mm	φ33.6*139.7mm
Components inside the box	Batter Cell: Gotion High Tech 32135 15AH, 3,2V A+ Grade Connection: 8 On Row . Number Of Batteries: 16 Nos. Battery Capacity: 12.8V, 60AH.	Batter Cell: Gotion High Tech 32135 15AH, 3,2V Connection: 8 On Row + 8 On a Raw 2 Level. Number Of Batteries: 32 Nos. Battery Capacity: 25.6V, 60AH.
Battery isolation details of 3 layers	PC Holder Blue Plastic Seal Aluminum heat sink	PC Holder Blue Plastic Seal Aluminum heat sink
Function	Quick Charge Display screen Easy replacement Air Valve	Quick Charge Display screen Easy replacement Air Valve
Controller details	DM80 : All in one All in two 1L All in two 1L Classic HUAHUIYUAN: Solar Chair	DM160: All in two 2L All in two 2L Classic 200W: All in two 2L Fold light



Model No.		SOLARA -003-01	
Item		All in Two Solar Street Light 1 Way	
PV Power (W)	180W (18V)	Solar Panel Size	980 x 980 x 30mm
Material		Monocrystalline Silicon	
Battery		60Ah, 12.8V (LiFePO4), >3000 cycles	
Controller		SRNE MPPT DM160	
LED Brand	PHILIPS	Power (W)	60W
Luminous Flux (lm)	11000 lm, 180 lm/W	Chip size	SMD 5050
CCT (K)		1800K ~ 6000K, Ideal 4000K	
Work Mode		Programmable/ Supplied with pre programmed - First 6 Hours 100%, Next 6 Hours 50%	
Protection Grade	IP65/ IK08	Control Unit	Replaceable
Material	Aluminum	Diffuser	Polycarbonate Lens
Pole Height	Preferably 5 - 8Mtrs	Operating Temp.	- 10°C ~ +80°C
Warranty		5 Years	

