

Nominal Flow	3.0 m ³ /hr @ 45 m
Flow Range	0.5 ~ 6.5 m ³ /hr
Head Range	5 ~ 65 m

Solar pumping System

Note:

SAMKING solar motor powers the new system for the supply of clean water based on the most widely available renewable energy, the sun. It is designed for easy use and requires no maintenance. It is the ideal solution for supplying water in remote areas, where the normal power supply of electricity from the power grid is inconsistent or completely unavailable


Parameter

Location:	United Arab Emirates;Du	Water Temp:	25°C		
	bai				
Required daily output:	20m ³ /day	Dirt loss:	3%	Motor lenght:	50
Pipe type:	Plastic	Static Head:	35m	Pipe length:	20m


Products

Submersible pump	1pc;4SPW3-5P (0.75HP DC)
Solar panel	3pc;900Wp;300w x3pcs
Motor cable	
Pipeline	20m;Pipeline
Accessories	


Daily output in average month (23.5) m³/day



Solar Panel Wiring




Sizing Layout



H (Static head):	Vertical height from the dynamic water level to the highest point of delivery.
B (Drawdown):	Lowering of water level depending on flow rate and recovery rate of the well.
D (Pipeline inner diameter):	
L (Pipe length):	Entire pipeline from the pump outlet to the point of delivery. Elbows and armatures must be added as an equivalent length of pipeline.
M (Motor cable):	The cable between controller and pump unit.
T (Tilt angle):	Angle of the PV generator surface from the horizontal plane.

System Layout



- | | |
|---|--------------------------|
| 1、Solar panels | 7、Solar water pump |
| 2、SPD(DC) Surge Protection Device | 8、Traction rope |
| 3、Check valve | 9、Float Switch(For Tank) |
| 4、Wiring Package(Epoxy Resin Wiring Package or Heat Shrinkable Tube Wiring Package) | 10、Controller |
| 5、Float Switch (For Dry Protection, Optional) | 11、GPRS (Optional) |
| 6、Sacrificial Anode | |

Note:

- 1、 Please read the manual carefully for all installation accessories, Please contact factory if you need all the above accessories.
- 2、 Float Switch for Dry Protection is Optional for centrifugal pump, Because the centrifugal pump system has its own dry protection; However, for helical pump, it must be installed.
- 3、 The pump shall be installed at least 1.5m away from the bottom of the well;
- 4、 It is recommended to install a check valve every 70m of the vertical height of the pipeline.

4SPW3-5P (0.75HP DC)

Solar Submersible Pump System

System Overview

Head	max. 72m
Flow	max. 108L/min
Recommend Max input Power	max. 1 kW
Minimum well diameter	min 4 inch
Pump discharge	Rp 2"
Efficiency Max	%

Product advantage

- .Stainless steel Motor: AISI 304;
- .BLDC High Efficiency Motor;
- .External Controller;
- .Only could powered by DC power ;
- .Voltage/Current/Power/RPM/Display;
- .Encapsulated water filled motor(No pollution risk);
- .Soft start running makes system's life longer;
- .Thrust bearing system;
- .Reverse protection(reverse + and - is fine);
- .Over load protection/over current protection/over power protection;
- .Voltage:65-110Vmp/ 150VOC;
- .Dry protection(No additional float sensor required);

Technical Data

Controller 4SPW3-5P (0.75HP DC)

- .External Controller: 3SPW-0.75HP;
- .MPPT Efficiency Max.98%;
- .Voltage:65-110Vmp/ 150VOC;
- .Enclosure class:IP65;
- .Error report;
- .Losing-Phase protection.
- .Over temperature protection;

Motor 3SPW-72V-0.75HP DC

Voltage	DC max.VOC 150V DC Vmp 65-110V
Current	max.DC 15A
Motor Efficiency	max.85%
WaterTemp	max.40°C
Insulation class	F
Enclosure class	IP X8
Submersion	max.150m
Required cooling flow	0.5L/s
Speed	1000-4000

Pump End

- .Plastic impeller ;stainless steel shell;
- .Non-return valve
- .Centrifugal pump;

Standards



Note:

**Recommended 3 Pcs of 340W Solar Panels in Series;


**The Controller is IP 65 Rated however it is recommended that it is not mounted in direct sunlight;

**VOC (V) Volts open circuit nothing connected;Vmp (V) Volts maximum power point under load;Exceeding limits may cause serious harm or irreparable damage.



4SPW3-5P 0.75HP

Flow max.108L/min; Head max.72m; BSP 2",Centrifugal pump (Plastic impeller)



HEAD (m)	INPUT POWER (WATTS)				
	200	400	600	800	1000
	Flow (L/min)				
0	68	85	97	106	108
10	50	68	82	95	98
25	13	50	69	83	82
35		25	52	67	67
45			31	52	50
55				31	33
65				0	8

4SPW3-5P

Dimensions and Weights

