



Deutsche
Qualität
Garantiert



CMER-132BDS 610W-630W

More power, less degradation


23.34%
MAXIMUM EFFICIENCY

132
HALF CELLS

30 YEARS
Performance Warranty


up to **30 YEARS***
Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



- LID
RESISTANT
- PID
RESISTANT
- SALT CORROSION
RESISTANT
- SAND
RESISTANT
- AMMONIA
RESISTANT
- HIGHLY STABLE
AND TOUGH

OUR PERFORMANCE WARRANTY




SYSTEM AND PRODUCT CERTIFICATIONS



www.ae-solar.com

AE CMER-132BDS 610W-630W

N-TYPE TOPCON TECHNOLOGY PV MODULE



Electrical specifications (STC*):

	P_{max} (Wp)	610	615	620	625	630
Nominal max. power	P_{max} (Wp)	610	615	620	625	630
Maximum operating voltage	V_{MPP} (V)	40.80	41.10	41.40	41.70	42.00
Maximum operating current	I_{MPP} (A)	14.95	14.96	14.98	14.99	15.00
Open-circuit voltage	V_{oc} (V)	49.00	49.30	49.60	49.90	50.20
Short-circuit current	I_{sc} (A)	15.96	15.99	16.03	16.06	16.09
Module efficiency	η (%)	22.60	22.79	22.97	23.16	23.34
Power tolerance	(W)	0~+5				
Maximum system voltage	(V)	1500				
Maximum series fuse rating	(A)	30				

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance Pmax: ±3%

Electrical specifications (NMOT*):

	P_{max} (Wp)	467	470	474	478	482
Nominal max. power	P_{max} (Wp)	467	470	474	478	482
Maximum operating voltage	V_{MPP} (V)	38.20	38.40	38.60	38.80	39.00
Maximum operating current	I_{MPP} (A)	12.23	12.24	12.28	12.32	12.36
Open-circuit voltage	V_{oc} (V)	46.50	46.80	47.10	47.40	47.70
Short-circuit current	I_{sc} (A)	12.88	12.88	12.90	12.93	12.95

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Bifacial electrical specifications

	610		615		620		625		630	
Max. power front-side $P_{max front}$ (Wp)	610		615		620		625		630	
Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Total equivalent power $P_{max equ}$ (Wp)	641	671	646	677	651	682	656	686	662	693
Module efficiency η (%)	23.73	24.86	23.93	25.07	24.12	25.27	24.32	25.48	24.51	25.67

*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

Mechanical and design specification

Cell type	n-Type TOPCon technology, half-cut cells
No. of cells	132
Bifaciality	80 ± 5%
Front cover	2.0 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	2.0 mm white glazed glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable (Including Connector)	1 x 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2382 mm x 1133 mm x 30 mm
Weight	33.7 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m ²
Snow load	5400 Pa or 550 kg/m ²
Fire rating	Class A (according to UL 790)

Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.29 %/°C
Temp. coefficient of V_{oc}	-0.24 %/°C
Temp. coefficient of I_{sc}	0.040 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	720 pcs / 40 HQ
Size / Pallet	1160 mm x 1140 mm x 2500 mm (Upright)
Weight	1241 kg / pallet

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.



+49 8231 978268 0
sales@ae-solar.com
www.ae-solar.com

AESOLAR
Messerschmittring 54
86343 Königsbrunn, Germany